

PSC-BL-M-RT-DC0 (-BLE) | Bi-level Dimming Microwave Sensor

Overview

- Microwave sensor 24.11 GHz
- 0-10V Bi-level Dimming. Manual options: 0% (OFF)*, 10%, 25% or 50% dimming
- Time delay 1 adjustable 5 sec to 30 min
- Time delay 2 adjustable 10 sec to ∞
- Active High/Low outputs for Relay drive
- 33ft (10m) diameter coverage pattern, at 10ft (3m) mounting height.
- Bluetooth add-on enables remote sensor programming, granular customization of dimming levels, time delays, high-end trimming
- Bluetooth add-on also enables smart phone fixture control, with sensor override for instant 0-10V dimming and on/off control*



Suffix “-BLE-FSR” is also in compliance with IC, AS/NZS and JAPAN for Radio Communication

Suitable for indoor and outdoor use



Applications

The PSC-BL-M-RT-DC0 actively emits microwaves at 24.11 GHz frequency and uses the Doppler shift of the return waves to detect motion.

The PSC-BL-M-RT-DC0 is a Class 2 Device designed to satisfy new CA Title 24 requirements for bi-level dimming of lighting fixtures. Using a 0-10V signal, the sensor is capable of dimming lighting loads down to 0%*, 10%, 25%, or 50%.

The sensor is suitable for a variety of indoor and outdoor applications. It supports fixture and ceiling mounts up to 12ft (3.6m) high. Both sensor and power pack are rated for use in temperatures ranging from -30° to 70°C and relative humidity from 90 to 95% at 30°C.

0-10V: 100mA to drive up to 50 LED sink drivers on 0-10V output.
High Vin-2.5V 100mA source
Low 100mA sink current

*For dim to off, Pacific PSC-AC-PP-200/300/400 Power Pack or LED dimming driver capable of dimming to off is required.

Sensor Operation

End users can manually program length of time delay, sensor range and dimming level using a series of dipswitches and trim pots. Simply remove the cover to gain access.

Bi-level Dimming:** 0-10V bi-level dimmer connects to 0-10V control on the LED driver. When motion is detected the sensor will bring lighting up to 100% lumen output. When no motion is detected for the length of TD1, the sensor will send a signal to dim lighting to a specific level set by the end-user. If no motion is detected for the length of TD2, the sensor will send a signal to shut off the light.

Relay Control: Two additional High and Low motion outputs can be used to control relays or other control circuitry.

Bluetooth smart and Bluetooth mesh: The Bluetooth Low Energy (BLE) enabled version pairs with an Android or iOS application to allow initial setup and subsequent sensor adjustments, beyond what the analog controls on the sensor can offer. The mobile application enables adjustment of sensor parameters such as time delay, dim level, sensitivity, ambient light level, and more. Additionally, features such as parameter profiles, manual dim control, and real-time feedback from the sensor can speed up configuration and provide custom user control. The Bluetooth Smart™ enabled sensors support mesh networking through a variety of software and wireless platforms.

Accessories

Power Pack: The PSC-BL-M-RT-DC0 operates on 12-24VDC input and requires a separate power pack such as the PacWave™ PSC-AC-PP-200/300/400.

This power pack incorporates a high current relay and a high voltage transformer which can accept universal input (100-305VAC).

Alternatively, the sensor can also operate with a driver that has an auxiliary output (12V).

** The sensor will dim the light if motion is not detected for the first time delay (TD1) and shut off the light if motion is not detected for the second time delay (TD2). TD2 will only count down after TD1 has expired and the light has dimmed. If motion is detected during TD2, the light will return to full output, and TD1 will restart.

If using a power pack, the sensor will tell the power pack to shut off the driver after TD2 expires to turn off the light. If using a dimming driver without a power pack, the sensor will try to dim down to 0% upon expiration of TD2.

Since one trim pot configures both TD1 and TD2, a fixed TD2 is set to each value of TD1. See page 2 for the corresponding values.


How to Order

Model No.	Description	Input Voltage	Output
PSC-BL-M-RT-DC0	Bi-Level Microwave Remote Mount Occupancy Sensor	12-24VDC	0-10VDC Control High Control Low
PSC-AC-PP-200	Dimming Power Pack for Fixture Mount	100-277VAC	12.5VDC
PSC-AC-PP-700C	Power Pack for Fixture Mount	100-277VAC	12.5VDC
PSC-AC-PP-400	Power Pack for Fixture Mount no Relay	100-277VAC	12.5VDC
Add Suffix for options:			
-BLE	For PacWave Standalone Bluetooth Enabled Version		
-BLE-SR	For Bluetooth Mesh in TruBlu™ Enabled Version		
-BLE-CB	For Bluetooth Mesh in Casambi Enabled Version		
/IC	with Connector, see page 3, Lead Option B		

Summary	
Sensor Type	Microwave occupancy sensor
Input Voltage Current Consumption	12-24VDC 60mA sensor (85mA w/ BLE)
0-10V Output	100mA, up to 50LED sink drivers
High	Vin-2.5V 100mA source
Low	100mA sink current
Mounting Height	Fixture or ceiling mount 10ft (3m)
Max Range*	16ft (5m) radius
Time Delays (TD1/TD2)**	5 sec/10 sec, 5 min/30 min, 15 min/45 min, 30 min/60 min, 10 min/∞****
Photocell Sensitivity**	N/A
Max Bluetooth Range***	49 ~ 65ft (15 ~ 20m)
Operating Temperature	-30° C to 70° C
Storage Temperature	-40° C to 80° C
Relative Humidity	90-95% non-condensing at 30°C
Color	White
Warranty	5 years


*Results may vary based on mounting height, angle, floor material, and line of sight
 *If installed inside enclosure lens, detection range adversely affected by the type and density of the material used in the fixture lens or cover
 **Photocell can be activated through optional Bluetooth version only.
 **Bluetooth versions enable adjustment of sensor parameters such as time delay, dim level, sensitivity, ON/OFF daylight detection, and more.
 ***Bluetooth Range is highly dependent on the integration of fixtures, surrounding environment and conditions. It is recommended to conduct testing for range accuracy.
 ****If TD1 is set to 10 min, TD2 will never expire. So the light will remain at the dim level for as long as motion is not detected.

Physical Dimensions



Drawings are Not to Scale

Wiring Diagram



Note: If using a power pack other than PSC-AC-PP-200, connect either Control Hi or Control Low, depending on power pack relay circuitry.

Settings Adjustment


Dipswitch 1	Dipswitch 2	DIM Level
OFF	OFF	OFF
OFF	ON	10%
ON	OFF	25%
ON	ON	50%

Trim pots


Trim pot #1 on left adjusts time delay. Trim pot #2 on right adjusts motion detection range and sensitivity. Turn clockwise to increase, turn counter-clockwise to decrease.




Detection Area for 10ft (3m Mounting Height)



Detection Area for 3ft (0.9m) Sideways Mounted Heights




Low Sensitivity




High Sensitivity

Lead Options:

Option A (Standard):



Option B (IC):



① Matching male and female connector: TE 794617, 794616 or equivalent